



HURRICANE 300ES

HURRICANE 300ES SPECIFICATIONS

• TRAILER MOUNTED

2" x 4" rectangular tube frame with front steering axle; four, 5 lug 20.5 x 8 x 10" tires

• POWER SOURCE

Honda gasoline engine, 24 HP at 3600 RPM

• DRIVE SYSTEM

Direct drive quick flex couplings (no belts)

• VACUUM AIR FLOW (blower)

Roots Dresser 450 CFM, 15" hg, with guard

• FILTRATION SYSTEM

Individual collection cyclone and an individual baghouse cyclone. Baghouse -3 Teflon coated, quick change filter bags with manual reverse pulse air cleaning. Discharge of material is manual.

• FUEL SYSTEM

6 gallon plastic gasoline tank with sight gauge

• INSTRUMENT PANEL

12 volt key start, choke, and throttle control

STANDARD EQUIPMENT

- Paint-one color (custom lettering available)
- Lifting eyes
- Wet or dry operation
- Front steering axle for pulling and maneuvering

OPTIONS

- Skid mount
- Low oil pressure shut down
- Sound package (silencer upgrade)
- Filter cartridge vs. cloth filter bags
- DOT legal trailer with lighting and electric brakes
- Tool boxes
- Hour meter

WEIGHT AND DIMENSIONS

- 1,650 pounds
- Length: 9'10" with steering handle extended (7'2" retracted)
- Width: 4'3"
- Height: 8'4" with cyclones; 7'0" without cyclones

Information in this document
is subject to change without notice.



Industrial Air Solutions, Inc.
6300 Limousine Drive, Suite 120
Raleigh, NC 27617

Toll Free (USA) 877-844-3293

Fax 919-518-1667

E-mail info@industrialairsolutions.com

www.industrialairsolutions.com