



# HURRICANE 500EM

## **HURRICANE 500EM SPECIFICATIONS**

- **SKID MOUNTED**

4" X 8" rectangular tube frame, lifting eyes, fork truck tube pockets

- **POWER SOURCE**

100 HP electric motor, 460 volt, 3-phase, hostile duty

- **VACUUM AIR FLOW (blower)**

Roots Dresser 2350 CFM capable of 27" Hg, 5 belt driven, with guard

- **FILTRATION SYSTEM**

Cyclonic separation. Baghouse - 37 Teflon coated, quick change filter bags with continuous reverse pulse air cleaning.

High efficiency blower safety filter.

- **INSTRUMENT PANEL (NEMA 3R)**

Soft start package, push button on/off switch with indicator light, disconnect lever, air pulse on/off switch, material dump on/off switch.

## **STANDARD EQUIPMENT**

- Paint-one color (custom lettering available)
- Wet or dry operation
- Automatic cone vibrator

## **OPTIONS**

- 150 HP electric motor
- Slide gate discharge
- 16" manhole on baghouse
- Auger in hopper (cone)
- Hydraulics (lift cylinder)
- HEPA filtration
- Tool box
- Emergency stop button
- Air compressor - 120 PSI
- Trailer mounted to DOT standards

Information in this document  
is subject to change without notice.



**Industrial Air Solutions, Inc.**  
6300 Limousine Drive, Suite 120  
Raleigh, NC 27617

**Toll Free (USA) 877-844-3293**

Fax 919-518-1667

E-mail [info@industrialairsolutions.com](mailto:info@industrialairsolutions.com)

[www.industrialairsolutions.com](http://www.industrialairsolutions.com)



**HURRICANE**

**500EM**

**DIMENSIONS**

WIDTH 76" WEIGHT 8,500 lbs

