

elephant-vac

MODEL EV-2S SKID MOUNTED VACUUM

Toll Free (USA) 1-877-844-3293



Elephant-Vac Skid Mounted Litter Vacuum is ideal for litter cleanup on roadsides, in parking lots, along fencelines, in ditches anywhere litter accumulates. Use on your existing vehicle keeps equipment purchase cost down. The vacuum unit is self-contained; it operates without connection to a vehicle.

Model EV-2S can be installed in the back of a pickup truck, on a dump truck tailgate, in the bed of an industrial truck, or on a utility trailer. It has a flat base with bolt holes and chain hooks for secure attachment. Fork lift pockets in the support frame allow easy placement and removal .

The vacuum can be mounted in any position for pick-up on either side or the rear of the vehicle. The standard hose covers an area from the side of the vehicle to six feet out. Reach can be extended to ten feet with Model BX4 - Four Foot Boom Extension.

Operation is usually by two people, a driver and a vacuum operator. In some applications with a heavy concentration of debris, it is used by one operator. Model 15X - Hose Extension Kit quick-connects to the end of the standard hose to reach a larger area, or under benches and among plants and shrubbery.

Model EV-2S is powered by an 9.0 hp, electric start, fuel efficient Kawasaki engine. It operates all day on less than 3 gallons of gasoline, providing a long range for outdoor cleanup.

The unit comes with an extra long hose to reach the ground when mounted in a truck bed. The optional BX4 Four Foot Boom Extension includes a hose extension and allows further reach for special applications. The boom extension can be provided in other, longer lengths for special applications.

MODEL EV-2S SKID MOUNTED LITTER VACUUM

specifications

SYSTEM TYPE:	Tank type vacuum. Debris does not pass through the impeller.
ENGINE:	Kawasaki 9.0 hp (6.7 kw). 17.5 cu. in. (286 cc) displacement. Single cylinder, overhead valves, air cooled, electric start.
FUEL:	Regular gasoline. 3.0 gallon (11.3 liter) capacity.
STARTING:	Key ignition switch.
OPERATION:	Cable throttle control.
IMPELLER:	Cast aluminum. High-speed balanced. Top mounted for maximum airflow and dust control.
IMPELLER SPEED:	1800 - 4000 rpm variable.
PERFORMANCE:	Airflow: 2300 cfm (65 cmm). Velocity: 6500 fpm (119 kph).
FILTER SCREEN:	High strength steel. Rotating -- self-cleaning. Optional cloth filter bag for air outlet.
HOSE:	8 inch (20 cm) diameter, 15 foot (3.8 meter) long. Flexible rubber, helical spring wire reinforced.
CONTAINER:	Heavy gauge galvanized steel, painted, 60 gallon (227 liter) capacity.
LINER:	Heavy gauge polyethylene.
BAGS:	22" x 20" x 50" x 3 mil (56 cm x 51 cm x 127 cm x .08 mm). Black polyethylene in attached canister.
BATTERY:	Group U1 type in plastic enclosure.
FRAME:	Heavy wall steel tubing. Welded construction.
DIMENSIONS:	30.5" (78 cm) wide x 48" (123 cm) long not incl. hose. 66" (167 cm) high to top of engine.
WEIGHT:	375 lbs (170 kgs).

The manufacturer reserves the right to change specifications at any time without notice. One year limited warranty.



INDUSTRIAL AIR SOLUTIONS, INC.

Toll Free (USA) 1-877-844-3293

P.O. Box 90246 • Raleigh, NC 27675
Raleigh 919-844-3293 • Fax 919-518-1667
www.industrialairsolutions.com
Email info@industrialairsolutions.com