


253 Magnum Scrubbe



Disk

Cylindrical

BODY CONSTRUCTION/DIMENSIONS

Tank Construction	(7/16") Roto-Poly	(7/16") Roto-Poly
Frame Construction	3/16" (Steel)	3/16" (Steel)
Drive Wheel	(2) 12" dia. x 3.5"	(2) 12" dia. x 3.5"
Casters	(2) 5" dia. x 2"	(2) 5" dia. x 2"
Body Dimensions (L x W x H)	56" x 24" x 43"	56" x 24" x 43"
Width (squeegee)	35", 38" or 45"	35", 38" or 45"
Weight (w/out batteries)	498 pounds	494 pounds
Weight (w/standard batteries)	875 pounds	886 pounds

BRUSH/PAD SYSTEM

Brush/Pad Diameter	26D (2) 13" 30D (2) 15" 34D (2) 17"	24C (2) 22" x 5.5" 27C (2) 25" x 5.5" 30C (2) 28" x 5.5" 34C (2) 32" x 5.5"
Motor Power (standard)	(2) 0.75 hp / 200 rpm	24/27 (2) 0.75 hp / 350 rpm
Motor Power (HD Option)	(2) 1.0 hp / 200 rpm	30/34 (2) 1.0 hp / 350 rpm
Brush Speed	200 rpm	750 rpm
Brush Pressure	0-250 pounds	0-250 pounds
Brush Pressure Settings	(1-5) automatic	(1-5) automatic

BATTERY SYSTEM

Battery AH Rating (Standard)	210 AH	210 AH
Battery AH Rating (Optional)	Up to 325 amp hour	Up to 325 amp hour
Battery Run Time	Up to 5 hours	Up to 5 hours
Charger (110v / 60 Hz / auto)	24-v / 25-amp	24-v / 25-amp

SOLUTION SYSTEM

Solution Tank Capacity	30-gallons	30-gallons
Solution Flow Rate	0 – 0.75 gal/min	0 – 0.75 gal/min

RECOVERY SYSTEM

Recovery Tank Capacity	30-gallons	30-gallons
Vacuum Horsepower	0.8 hp / 3-stage	0.8 hp / 3-stage
Vacuum (Water Lift / Cubic ft/min)	68" / 72 cfm	68" / 72 cfm

DRIVE SYSTEM

Transaxle Description	0.75 hp, gear / sealed	0.75 hp, gear / sealed
Speed Control	0 – 230 ft/min	0 – 230 ft/min

PRODUCTIVITY

Cleaning Width & Rate/Hour	26" / 26,000 sq.feet / hour	24" / 24,000 sq.feet / hour
	30" / 30,000 sq.feet / hour	27" / 27,000 sq.feet / hour
	34" / 34,000 sq.feet / hour	30" / 30,000 sq.feet / hour
		34" / 34,000 sq.feet / hour

all specifications are subject to change without notice.