

**Models
290/350**

**Compact Rider Scrubber
Specifications**



290

350

BODY CONSTRUCTION/DIMENSIONS

Tank Construction	Poly (3/8")	Poly (3/8")
Chassis Construction	3/16" Steel	3/16" Steel
Rear Wheels	12" x 5"	12" x 5"
Casters	(2) 6" Diameter x 2"	(2) 6" Diameter x 2"
Dimensions (L x W x H)	62" x 29" x 55"	62" x 35" x 55"
Squeegee Size	30", 35" OR 38"	38" OR 45"
Weight (w/out batteries):	750 lbs	810 lbs
Weight (w/ batteries)	1260 lbs	1320 lbs

BRUSH/PAD SYSTEM DISK

Brush/Pad Diameter	(2) 15.5 inches	(2) 18 inches
Motor (hp and rpm)	(2) 1.0 hp / 350 rpm	(2) 1.0 hp / 350 rpm

BRUSH/PAD SYSTEM CYLINDRICAL

Brush Size (length / diameter)	(2) 26"	(2) 28" or 32"
Motor (power / speed)	(1) 2.0 hp / 850 rpm	(1) 2.0 hp / 850 rpm
Brush Pressure	0-200 lbs	0-250 lbs

BATTERY SYSTEM

Battery AH Rating	396 amp hour	396 amp hour
Battery Run Time	Up to 6 hrs	Up to 6 hrs
Charger (110v / 60 Hz / auto)	24v / 36 amp	24v / 36 amp

SOLUTION SYSTEM

Solution Tank Capacity	38 gallons	38 gallons
Solution Flow Rate	0-1.5 gal/min	0-1.5 gal/min

RECOVERY SYSTEM

Recovery Tank Capacity	40 gallons	40 gallons
Vacuum Horsepower	1.0 hp, 3-stage	1.0 hp, 3-stage
Drain Hose	2.0" Diameter	2.0" Diameter
Cleanout Door (Optional)	5.0"	5.0"
Water-lift	70 inches	70 inches
Demisting Chamber	5 gallons	5 gallons

DRIVE SYSTEM

Transaxle Description	2.0 hp, sealed	2.0 hp, sealed
Speed Control:	Variable 0-320 ft.	Variable 0-320 ft.

PRODUCTIVITY

Cleaning Width	29 inches	35 inches
Cleaning Rate/Hour	25,000 sq. ft/hour	42,000 sq. ft/hour
Sound Level	75dBA @ Operator's Sitting Position	75dBA @ Operator's Sitting Position

All specifications are subject to change without notice.